

STP-FP-101 v.003 - 01/01/2020

Novexpans

HFC 365mfc/HFC 227ea (87/13)

PERFORMANCES

The **NOVEXPANS™ HFC 365mfc/HFC 227ea (87/13)** is a blend of HFC 365mfc and HFC 227ea with guaranteed specifications used as an expansion agent in **polyurethane foam expansion**.

The foams resulting of the **NOVEXPANS™ HFC 365mfc/HFC 227ea (87/13)** show **good mechanical resistance**, a **low thermal conductivity** and a **fine cellular structure**.

The packaging in bottles or containers ensures the stability of the blend concentration.

The **high concentration of the HFC 227ea increases its safe use**. It is **on-flammable**.


SPECIFICATIONS

Standard characteristics	Limit values
Appearance	Clear
Composition:	
HFC 365mfc	87 ± 2 % weight
HFC 227ea	13 ± 2 % weight
Water content	≤ 100 ppm weight
Non volatile residue	≤ 100 ppm weight

CHARACTERISTICS

		Units	Values
Molecular weight		g/mol	151*
Boiling point	initial, below 1.013 bar	° C	23
Liquid density	at 20°C	kg/dm ³	1.29*
	at 50°C	kg/dm ³	1.20*
Absolute pressure	at 20°C	bar	0.9*
	at 50°C	bar	2.2*
Latent heat of vaporization	at boiling point	kJ/kg	181*
Flash point	closed cup	° C	none
λ	at 25°C	mW/m.K	11.2*

**calculated*



PACKAGING

	Drum	Container
Capacity (liter)	217	930
Tare (kg)	22	460
Load (kg)	240	1000
Diameter (mm)	585	860
Height (mm)	880	2330
Outflow external diameter (mm)	¾" & 2"	26.1
Tap: right pitch (mm)	---	1.814
Test pressure (bar)	---	33

- Packaging technical characteristics available upon request to the commercial department.
- Feasibility of filling packaging of the customers if they are in conformity with the legislation.
- Contact us for any other specific packaging.

STORAGE AND SHELF LIFE


Precautions for handling and storage:

French plants are controlled by the regulation of listed Establishments and have to comply with it (or with the local legislation).

- All packaging will be stored in a dry, well-ventilated, easily accessible place, sheltered from sunlight and bad weather, away from any ignition source.
- It is recommended to store all packaging either in a specific place or isolated and sheltered by a fence.
- All packaging and piping will be grounded to discharge static electricity.
- Leak detectors, put at ground level, will be connected to an audible alarm, which will trigger in the event of leaks.
- The whole equipment will be tested with an appropriate leak detector before use.
- Material and electrical equipment in an explosive atmosphere will comply with the regulations (*grounding, equipotential bonding, ATEX material*).

Climalife can study the set up and assembling of your storage tanks, piping, and pumps, according to the prevailing regulations.

Shelf life: unlimited (if appropriate storage conditions).



CONDITIONS OF USE

Please refer to the Material Safety Data Sheet (MSDS) before using the product.

Workers handling the product should be trained about risks and preventive measures.

The product is compatible and not compatible with:

COMPATIBILITY	NON COMPATIBILITY
<p>Plastics:</p> <ul style="list-style-type: none">▪ Neoprene <p>Metals:</p> <ul style="list-style-type: none">▪ Ordinary steel▪ Stainless steel	<ul style="list-style-type: none">▪ Strong bases▪ Oxidizing agents▪ Combustive agents▪ Metal powders▪ Alakli metals

The information above is intended as a guide only. We assume no liability for its accuracy on its use. The user should make its own tests under its conditions in order to determine the suitability of any compound in a peculiar application.

Measures while handling:

- Collect vapors at emission point,
- Use spark-free tools (*beryllium bronze*),
- Ground the equipment,
- Work in a well ventilated premises to avoid accumulating static discharges.

HEALTH SAFETY AND ENVIRONMENT (HSE)

Consult the Material Safety Datasheet (MSDS) on the website: www.quickfds.com

This data is based on information that the manufacturer believed to be reliable and offered in good faith. On no account, Climalife will be responsible for special, incidental and consequential damages. The user is responsible, to the Administrative Authorities (Regulation of the listed establishments for the protection of the environment), for the conformity of his installation.